

LIOS GRIGIOFF

Restoring solution for weather woods



Description

Specific restoring water based solution for external wood or wood structures (decking, furnitures, etc). It does not degrade rubbers and expansion joints. CERTIFIED BIODEGRADABLE AND ECOTOXIC OECD 301-F OECD 202:2004

Characteristics

Mixture ratio	single-component
Application temperature	+10°C ÷ +25°C
Application	spray / roller 8 mm / brush
Coverage	25 m ² /L (depending to the wood absorption)
Sanding	not for sanding
Storage stability	1 year ⁽¹⁾
Packaging	1 L - 5 L
Tool cleaning	water

1 in original sealed containers at temperatures between +10°C and +25°C

How to use

It is advisable to make a preliminary test before the application. Shake well the bottle before the use. If the surface temperature is too high, especially during the summer season, or the weathered wood to be treated is dry, wet the surface with water before the application of LIOS GRIGIOFF.

Spray LIOS GRIGIOFF directly on the surface to be treated, let it act for 5-10 minutes, than remove the patina by brush. After brushing wash the surface with water.

Some weathered surfaces have to be treated twice.

After the restoring with LIOS GRIGIOFF and complete dryng, apply two coats of LIOS SUNDECK WOOD OIL or LIOS SUNDECK W OIL (see relatives technical data sheets).

Notes: it is possible to use a buffing machine or a water set to remove the patina formed

Warnings

Wear protective gloves and glasses during the application.

Label elements

· Causes serious eye irritation.· Causes skin irritation.

· If medical advice is needed, have product container or label at hand.· Keep out of reach of children.· Wash thoroughly with water after use.· Wear protective gloves / protective clothing / eye protection / face protection.· If skin irritation occurs: Get medical advice / attention.



Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_LIOS_GRIGIOFF.pdf