

LIOS SUNDECK WOOD OIL

Impregnator for outdoor wooden floors



Description

LIOS SUNDECK WOOD OIL is an outdoor wood impregnator particularly recommended for the treatment of outdoor wooden floors (swimming pool edges, verandas, walkways), window and door frames, fences and canopies made of wood. It contains natural and synthetic oils, with the addition of UV ray absorbers and special anti-ageing ingredients against the wood decay. It also protects wood against attack of wood-eating insects. It doesn't crack. Also available in LIGHT version, which doesn't alterate the natural colour of wood, particularly indicated for the treatment of south-american species (i.e. IPÉ Lapacho, Tobacco etc.) and other similar types of outdoor woods painted in autoclave (usually green colour). Doesn't degrade rubbers and expansion joints. It is recommended anyway to make some tests before application.

Characteristics

Mixture ratio	single-component
Application temperature	+10°C ÷ +25°C
Application	brush, spray, immersion
Thinning (if necessary)	Lios Solv
Coverage	1 L/13 mq. ca.
Dust dry	6 h ⁽¹⁾
Fingerprint dry	24 h ⁽¹⁾
Sandpapering	do not sand
Storage stability	1 year ⁽²⁾
Packaging	1 L - 5 L - 10 L - 25 L
Tool cleaning	Lios Solv

- at 20°C and 65% R.H.
- in original sealed containers at temperatures between +10°C and +25°C

Versions available

STANDARD: slightly colored in order to give a warm tone to the decking.

LIGHT: transparent to keep the natural wood color.

NO SLIP: certified UNI CENT/TS 15676:2008 - EN 14342.

IGNIFUGO: certified CFS1 according to EN ISO 9239-1 and EN ISO 11952-2 on Ipé

How to use

Shake well before use. Before applying LIOS SUNDECK WOOD OIL, prepare the wood, preferably with 120/150 sandpaper. For outdoor floors, in order to obtain a non-slip effect when floor is wet, it's recommended to sand with 60/80 grit sandpaper and to apply our specific product LIOS SUNDECK WOOD OIL NO SLIP 14342. Apply the first coat of LIOS SUNDECK WOOD OIL. Apply a second coat of the product after 24/48 hours, without sanding.

Warnings

Cloths, sponges, brush used for the application (even sanding dust), must be soaked immediately after use in order to avoid the risk of self-ignition.

Cleaning and general maintenance

To wash and clean outdoor floors, use LIOS SUNDECK SOAP (nourishing detergent) following the instructions for use. It efficiently removes dirt, traces of chlorine and salt etc.

Safety and risk information

Xn
N

· FLAMMABLE. · MAY CAUSE SENSITIZATION BY SKIN CONTACT. · VERY TOXIC TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT. · HARMFUL: MAY CAUSE LUNG DAMAGE IF SWALLOWED. · REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING.

· KEEP OUT OF THE REACH OF CHILDREN. · AVOID CONTACT WITH SKIN. · DO NOT EMPTY INTO DRAINS. · WEAR SUITABLE GLOVES. · IF SWALLOWED, SEEK MEDICAL ADVICE IMMEDIATELY AND SHOW THIS CONTAINER OR LABEL. · AVOID RELEASE TO THE ENVIRONMENT. REFER TO SPECIAL INSTRUCTIONS/SAFETY DATA SHEETS.

Contents: ALKANES C11-C15 ISO ; 2-OTTIL-2H-ISOTIAZOLIN-3-ONE ; HYDROXYPHENYL BENZOTRIAZOL DERIVATIVES;

Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_LIOS_SUNDECK_WOOD_OIL.pdf