

Technical Datasheet

Item Code: PPAR001X | Rev.: 2015-11-1

DILUENTE PULIPAR W

Water-based liquid detergent for removing of fresh adhesive from prefinished wooden floor



¤Description

DILUENTE PULIPAR W is a odorless water-based liquid detergent and it is used for pre-finished wooden floor dirty with single or two-component adhesives after laying. DILUENTE PULIPAR W is effective on adhesives partially hardened for maximum 6 hours (at +20°C, 60% RH). In any case, it is important to intervene before complete adhesive hardening.

¤Characteristics

Mixture ratio	single-component
Appearance	straw-yellow liquid
Odour	odorless
Application temperature	+10°C ÷ +25°C
Thinning (if necessary)	ready to use
Application	cloth
Coverage	20-30 g/m²
Packaging	1 L
Storage stability	1 year ⁽¹⁾
1 in original sealed containers at temperatures between +10°C and +25°C	

¤How to use

Apply DILUENTE PULIPAR W directly on the glue. Let to act it for a few seconds and rub slightly with a cotton cloth keeping a rotary motion.

In the case of particularly resistant adhesive it is advisible to extend the contact time of adhesive/DILUENTE PULIPAR W, trying to avoid many mechanical actions, in fact the excessive scrubbing might alter the opacity of the pre-finished wooden floor.

The possible halos can be removed using a clean cloth dampened with DILUENTE PULIPAR W.

Sponge any excess with a dry cloth. Make always a preliminary test to verify the resistance of the finish to DILUENTE PULIPAR W.

¤Label elements



· Safety data sheet available on request.

¤Web link

Be sure to have the latest version of this technical data sheet downloadable also from the following link:



http://www.chimiver.com/tds/EN_DILUENTE_PULIPAR_W.pdf

These information are given from the best of our knowledge and technical experience. They are of general character and not binding in any way our company. Every single case should be put to a pratical test by the user who assumes the full responsability of the final result of his work.